

Food Machinery Lubricants



Application Keystone Product Operating Range Comments

FRUIT and VEGETABLE PROCESSING

BEARINGS, (Including Electric Motors)

(Normal Conditions)	Nevastane HT/AW 2	0 to 350°F	Plain and anti-friction bearings. Contains anti-wear, and adhesion additives. Water resistant and corrosion inhibited. Transparent, aluminum complex. NLGI 2, NSF/USDA H-1.
(Acid & Alkali Conditions)	Nevastane 5P7	0 to 300+°F	Low speed plain and anti-friction bearings, valves, cams, slides, and open gears. Translucent and extremely tacky. Excellent moisture resistance. NLGI 2, NSF/USDA H-1.
	Nevastane 2 Plus	0 to 350°F	(When less tack required) Superior water resistance and oxidation additives. White, tacky aluminum complex. NLGI 2, NSF/USDA H-1.
Oil Lubrication (Normal Conditions)	Nevastane AW 100	SAE 30/	General lubricating and rust preventive oil to lubricate bearings, guides, and chains. Available in "SAFEGARD" spray. NSF/USDA H-1.
	KLC 30	SAE 30/ AGMA 3	Premium quality, multi-use oils for hydraulics, bearings, chains, compressors, vacuum pumps and gearboxes requiring a straight oil. Contains anti-wear, anti-rust, oxidation, and anti-foam
(Acid & Alkali Conditions)	Nevastane AW 150	SAE 40	Water white oil that is adhesive, tacky and resistant to acids/alkalies therefore protecting parts against corrosion and wear. Uses include; plain and anti-friction bearings, chains and vacuum pumps. NSF/USDA H-1.
	Nevastane AW 100	SAE 30	General lubricating and rust preventive oil to lubricate bearings, guides, and chains. Available in "SAFEGARD" spray. NSF/USDA H-1.

CAN

CLOSERS

Feed Chains	GP Oils	SAE 20 & SAE 30	Tacky, rust-inhibited, contains extreme pressure additives and is moisture resistant. NSF/USDA H-2.
Bearings (Hand Gun)	Nevastane HT/AW 2	0 to 350°F	Plain and anti-friction bearings. Contains anti-wear, and adhesion additives. Water resistant and corrosion inhibited. Transparent, aluminum complex. NLGI 2, NSF/USDA H-1.
	Nevastane 2 Plus	0 to 350°F	Superior water resistance and oxidation additives. White, tacky aluminum complex. NLGI 2, NSF/USDA H-1.



Food Machinery Lubricants



Application Keystone Product Operating Range Comments

FRUIT and VEGETABLE PROCESSING, continued

CAN CLOSERS, continued

Bearings (Automatic Lubrication System)	Nevastane HT/AW 0 & Nevastane HT/AW 1	0 to 350°F	Plain and anti-friction bearings. Contains anti-wear, and adhesion additives. Water resistant and corrosion inhibited. Transparent, aluminum complex. NLGI 2, NSF/USDA H-1.
	Keystone 120 L	SAE 90	Angelus Sanitary Can Machine Co. Manzel Lubricators. NSF/USDA H-2.
	Nevastane 90 Plus	SAE 90	Angelus Sanitary Can Machine Co. Manzel Lubricators NSF/USDA H-1.
Bearings (Acid & Alkali Conditions)	Nevastane 5P7	0 to 300+°F	Low speed plain and anti-friction bearings, valves, cams, slides, and open gears. Translucent and extremely tacky. Excellent moisture resistance. NLGI 2, NSF/USDA H-1.
	Nevastane 2 Plus	0 to 350°F	(When less tack required) Superior water resistance and oxidation additives. White, tacky aluminum complex. NLGI 2, NSF/USDA H-1
Drive Cases	Nevastane 90 Plus	SAE 90 AGMA 5	Contains anti-wear additives. NSF/USDA H-1. Check OEM recommendations for proper grade.
	Nevastane 140 Plus	SAE 140 AGMA 7	Contains anti-wear additives. NSF/USDA H-1. Check OEM recommendations for proper grade.
Can Covers in Stack	Nevastane 5	SAE 250	Semi-Fluid containing anti-rust additives. NSF/USDA H-1.

FILLERS

Fittings & Valves	Nevastane HT/AW 2	0 to 350°F	Plain and anti-friction bearings. Contains anti-wear, and adhesion additives. Water resistant and corrosion inhibited. Transparent, aluminum complex. NLGI 2, NSF/USDA H-1.
	Nevastane 2 Plus	0 to 350°F	Superior water resistance and oxidation additives. White, tacky aluminum complex. NLGI 2, NSF/USDA H-1.
Drive Cases (Normal)	Nevastane 90 Plus	SAE 90 AGMA 5	Contains anti-wear additives. NSF/USDA H-1. Check OEM recommendations for proper grade.
	Nevastane 140 Plus	SAE 140 AGMA 7	Contains anti-wear additives. NSF/USDA H-1. Check OEM recommendations for proper grade.
Vacuum Valves	Nevastane AW 100	SAE 30	General lubricating and rust preventive oil to lubricate bearings, guides, and chains. Available in "SAFEGARD" spray. NSF/USDA H-1.
Chains	GP Oils	SAE 20 & 30	Tacky, rust-inhibited, contains extreme pressure additives and is moisture resistant. NSF/USDA H-2

Food Machinery Lubricants



Application Keystone Product Operating Range Comments

FRUIT and VEGETABLE PROCESSING, continued

FREEZING/COLD STORAGE

Bearings (Grease)	Nevastane HT/AW 2	0 to 350°F	Plain and anti-friction bearings. Contains anti-wear, and adhesion additives. Water resistant and corrosion inhibited. Transparent, aluminum complex. NLGI 2, NSF/USDA H-1.
	Nevastane 2 Plus	0 to 350°F	Superior water resistance and oxidation additives. White, tacky aluminum complex. NLGI 2, NSF/USDA H-1.
Bearings (Oil Lubrication)	Nevastane SS 46	-6 to 400°F SAE 20	Semi-synthetic fluid for general lubrication, hydraulic system, chains, and rotary compressors. NSF/USDA H-1.
	Nevastane SS 100	8 to 450°F SAE 30	Semi-synthetic fluid for general lubrication, hydraulic system, chains, and rotary compressors. NSF/USDA H-1.
Refrigeration Compressors	Refrigeration Oil 1	-40 to 350°F	Low temperature lubricant for refrigeration compressors and air conditioning systems.

IN-LINE JUICE MACHINES

Fittings & Universal Joints	Nevastane HT/AW 2	0 to 350°F	Plain and anti-friction bearings. Contains anti-wear, and adhesion additives. Water resistant and corrosion inhibited. Transparent, aluminum complex. NLGI 2, NSF/USDA H-1.
	Nevastane 2 Plus	0 to 350°F	Superior water resistance and oxidation additives. White, tacky aluminum complex. NLGI2, NSF/USDA H-1.
Upper Gear Case	Nevastane 90 Plus	SAE 90 AGMA 5	Contains anti-wear additives. NSF/USDA H-1. Check OEM recommendations for proper grade.
	Nevastane 140 Plus	SAE 140 AGMA 7	Contains anti-wear additives. NSF/USDA H-1. Check OEM recommendations for proper grade.
Lower Gearbox	Nevastane AW 100	SAE 30	General lubricating and rust preventive oil to lubricate bearings, guides, and chains. Available in "SAFEGARD" spray. NSF/USDA H-1.