

Food Machinery Lubricants



<i>Application</i>	<i>Keystone Product</i>	<i>Operating Range</i>	<i>Comments</i>
BAKERY OVENS			
Outside Oven	Nevastane HT/AW 2	0 to 350°F	Plain and anti-friction bearings. Contains anti-wear, and adhesion additives. Water resistant and corrosion inhibited. Transparent aluminum complex. NLGI 2, NSF/USDA H-1.
	Nevastane 2 Plus	0 to 350°F	Superior water resistance and oxidation additives. White, tacky aluminum complex. NLGI 2, NSF/USDA H-1.
Open Gears	Nevastane AW 1000	SAE 250	Water white oil used to lubricate open gears and chains where a tacky viscous oil is desired. NSF/USDA H-1.
	Nevastane 5P7	0 to 300+°F	Low speed plain and anti-friction bearings, valves, cams, slides, and open gears. Translucent and extremely tacky. Excellent moisture resistance. NLGI 2, NSF/USDA H-1.
General Oiling	Nevastane AW 100	SAE 30	General lubricating and rust preventive oil to lubricate bearings, guides, and chains. Available in "SAFEGARD" spray. NSF/USDA H-1.
Oven Chains	KSL 217	-20 to 450°F SAE 20W-50	Diester-base, high temperature oven chain and conveyor oil containing soluble molybdenum disulfide.