

Food Machinery Lubricants



<i>Application</i>	<i>Keystone Product</i>	<i>Operating Range</i>	<i>Comments</i>
PACKAGING			
Fillers (Valves)	Nevastane HT/AW 1	0 to 350°F	Plain and anti-friction bearings. Contains anti-wear, and adhesion additives. Water resistant and corrosion inhibited. Transparent aluminum complex. NLGI 2, NSF/USDA H-1.
	Nevastane HT/AW 2	0 to 350°F	Plain and anti-friction bearings. Contains anti-wear, and adhesion additives. Water resistant and corrosion inhibited. Transparent aluminum complex. NLGI 2, NSF/USDA H-1.
Can Closer Bearings (Hand Gun)	Nevastane HT/AW 2	0 to 350°F	Plain and anti-friction bearings. Contains anti-wear, and adhesion additives. Water resistant and corrosion inhibited. Transparent aluminum complex. NLGI 2, NSF/USDA H-1.
	Nevastane 2 Plus	0 to 350°F	Superior water resistance and oxidation additives. White, tacky aluminum complex. NLGI 2, NSF/USDA H-1.
(Automatic Lubrication System)	Nevastane HT/AW 0 & Nevastane HT/AW 1	0 to 350°F	Plain and anti-friction bearings. Contains anti-wear, and adhesion additives. Water resistant and corrosion inhibited. Transparent aluminum complex. NLGI 2, NSF/USDA H-1.
	Keystone 120 L	SAE 90	Angelus Sanitary Can Machine Co. Manzel Lubricators NSF/USDA H-2
	Nevastane 90 Plus	SAE 90	Angelus Sanitary Can Machine Co. Manzel Lubricators NSF/USDA H-1.
Drive Gearbox	Nevastane 90 Plus	SAE 90 AGMA 5	Contains anti-wear additives. NSF/USDA H-1. Check OEM recommendations for proper guide.
	Nevastane 140 Plus	SAE 140 AGMA 7	Contains anti-wear additives. NSF/USDA H-1. Check OEM recommendations for proper guide.
Can Covers in Stack	Nevastane 5	SAE 250	Semi-fluid containing anti-rust additives. NSF/USDA H-1.
Chain Drives	GP Oils	SAE 20 & SAE 30	Tacky, rust-inhibited, contains extreme pressure additives and is moisture resistant. NSF/USDA H-2.